

251 North Bridge Road Singapore 179102 Tel: 1800 - CALL LTA (1800 - 2255 582) Fax: (65) 6332 8223

Please Quote Our Reference

Number In Your Reply

Our Ref: LTA/DBC/R70.018.015

Date: 4 Sept 2017

#### CIRCULAR TO PROFESSIONAL INSTITUTIONS

**Dear Sirs** 

1

M&E CHECKLIST FOR BUS SHELTER, TAXI / PASSENGER PICK-UP SHELTER, PEDESTRIAN OVERHEAD BRIDGE (POB) AND COVERED LINKWAY FOR DESIGN ASPECTS AND M&E CHECKLISTS FOR COVERED LINKWAY FOR MAINTAINENCE ASPECTS

## Who should know

Building owners, developers, architects and engineers

### **Effective Date**

1 October 2017

#### M&E Plan Submission Checklist

- 1. As part of LTA's continual effort in streamlining and enhancing the plan approval process, we are pleased to announce the launch of two new checklists which are as follows:
  - M&E Checklist for bus shelter, taxi/passenger pick-up shelter, pedestrian overhead bridge (POB) and covered linkway to address the design aspects
  - ii. M&E Checklist for covered linkway to address the maintenance aspects.

This new initiative aims to facilitate understanding of the relevant guidelines and to help QPs to make reference when preparing submissions of M&E plans to LTA for approval.

2. We would like to take this opportunity to highlight to the industry that all M&E submissions would be deemed to have complied with our requirements when the QPs endorse the M&E checklists.



3. The M&E checklists would be made available in Annex 2A and 2B of RT COP for Street Works proposal relating to Development Works. All future submissions made shall include the "M&E Checklist for Bus Shelter, Taxi/Passenger Pick-up Shelter, Pedestrian Overhead Bridge (POB) and Covered Linkway" and "M&E Checklist for Covered Linkway" for their M&E submissions.

# **Enquiries**

4. We would appreciate it if you could convey the contents of this circular to the relevant members of your organisation and building owners/developers on the M&E Checklist. If you or your members have any queries concerning these checklists, please email either <a href="Chan Wing Yew@lta.gov.sg">Chan Wing Yew@lta.gov.sg</a> for design aspects or ONG Kok Chin@lta.gov.sg for maintenance aspect.

Thank you.

Yours faithfully

Hadi Wijaya

Deputy Director

Mechanical and Electrical

Services

Poo Say Yaw

Deputy Director

Commuter Facilities

&Systems Management

Quek Teck Beng

Deputy Director

Development & Building

Control Division



# **Distribution List:**

President

Singapore Institute of Architects

79/79A/79B Neil Road

Singapore 088904

President

Association of Consulting Engineers

Singapore

Thomson Road Post Office

PO Box 034

Singapore 915702

President

Institution of Engineers, Singapore

70 Bukit Tinggi Road

Singapore 289758

President

Singapore Real Estate Developers

Association

190 Clemenceau Avenue

#07-01 Singapore Shopping Centre

Singapore 239924

President

Singapore Contractors Association Ltd

1 Bukit Merah Lane 2 Construction House Singapore 159760

President

Board of Architects, Singapore

5 Maxwell Road #01-03

Tower Block, MND Complex

Singapore 069110

President

Professional Engineers Board

52 Jurong Gateway Road

#07-03

Singapore 608550

Group Director

Development Control

Urban Redevelopment Authority

45 Maxwell Road The URA Centre

Singapore 069118

Director

Building Plan & Management Division

**Building and Construction Authority** 

5 Maxwell Road #16-00

Tower Block MND Complex

Singapore 069110

Director

Planning & Design Development

Division

National Parks Board

Singapore Botanic Gardens

1 Cluny Road

Singapore 259569

Head

Infrastructure and Agency Unit

Development

and

Procurement

Department

Housing Development Board

HDB Hub

480 Lorong 6 Toa Payoh

Singapore 310480

Director Land and Planning Group

JTC Corporation

8 Jurong Town Hall Road

The JTC Summit

Singapore 609431

# M&E CHECKLIST FOR BUS SHELTER, TAXI / PASSENGER PICK-UP SHELTER, PEDESTRIAN OVERHEAD BRIDGE (POB) AND COVERED LINKWAY

Project:

		(√) Tic	k the appro	opriate box for all items
	Standard Requirements	Yes	NA	Remarks
1.	General			
1.1	Drawings are in A1 series.			
1.2	Site plan, location plan and layout plans showing road reserve line and LTA's maintenance boundary are included.			
1.3	The proposed installations provided are within LTA's maintenance boundary.			
1.4	Electrical installations above PUB drains are complied with PUB's requirements.			
1.5	Design calculations with design parameters and acceptance criteria are included.			
1.6	Technical data, catalogues, relevant test certificates / certificates of compliance from accredited testing facilities for proposed equipment, cables, materials and accessories are included.			
1.7	All electrical drawings, documents and design calculations are endorsed by Licensed Electrical Worker (LEW).			-
1.8	All lightning protection system drawings, documents and design calculations are endorsed by Electrical Professional Engineer (PE).			
1.9	Responses to LTA's previous comments are attached.			н
1.10	All additions/deletions/amendments are clouded.			
1.11	Commuter facilities M&E requirements stated in LTA's Architectural Design Criteria (ADC) Section 4 are complied with.			

2.	Electrical Distribution		
2.1	Design of the electrical distribution is complied with LTA's ADC requirements and drawings.		
2.2	Single line diagrams for OG box and/or distribution board are included.		
2.3	Electrical loading and cable sizing calculations are included.		
2.4	OG box details showing plan view, front view, back view, internal view, external view, sections and elevations are included.		
2.5	Type B MCB are provided for all outgoing circuits.		
2.6	Surge protection device is provided as per LTA's ADC requirements.		
2.7	SPPG approved OG Box location complete with the route of SPPG incoming cables are included.		
2.8	OG box is not in the path of commuter walkway and line of sight of commuters looking at the oncoming traffic (e.g. obstructing the sight of arrival bus)		1
2.9	HD uPVC pipes for installation of armoured cables from the OG box to the proposed commuter facilities are provided with straight run or with gradual long bends.		
2.10	HD uPVC pipes complete with draw wires with straight run or with gradual long bends are provided for advertisement panel for bus shelters.		
3.	Lighting Design and Light Fittings		
3.1	No up-lighters are to be provided.		
3.2	Lighting level simulation reports with lux plots (one meter apart) and dimensions of simulated areas correspond to the lighting layout plans are included.		
3.3	Lighting levels and uniformity ratio measured at the ground level are complied with LTA's ADC requirements.		
3.4	The maximum allowable power budget is complied with LTA's ADC requirements.		

3.5	LED type light fittings of weatherproof IP65, vandal proof minimum IK06, ultra-violet (UV) stabilised and colour rendering index of 80 to 89 with colour temperature between 2700K and 3000K are provided.		
3.6	Lighting layout plans and sections with detailed cable routes from the OG box to the respective light fittings are included.		
3.7	The layout arrangement of light fittings are generally in line with LTA's ADC drawings.		V
3.8	Alternate lighting circuits are provided.		
3.9	High covered linkway lighting circuits are complied with LTA's ADC drawings.		
3.10	Covered POB is provided with intelligent lighting detection system as complied with LTA's ADC requirements.		
3.11	Cross-sectional mounting details of the proposed light fitting to demonstrate ease of maintenance is provided.		
4.	<b>Lightning Protection System</b>		
5.72			
4.1	The lightning protection system is designed in compliance to SS 555 and SS551.		
4.1			
	compliance to SS 555 and SS551.  Lightning protection layout plans, sections and installations details, such as lightning bonding,	S	
4.2	compliance to SS 555 and SS551.  Lightning protection layout plans, sections and installations details, such as lightning bonding, earth pit, etc. are included.  Minimum 10mm thick aluminium honey comb roof panels complete with minimum 1 mm thick top panel are provided as air termination system	5	
4.2	compliance to SS 555 and SS551.  Lightning protection layout plans, sections and installations details, such as lightning bonding, earth pit, etc. are included.  Minimum 10mm thick aluminium honey comb roof panels complete with minimum 1 mm thick top panel are provided as air termination system for the lightning protection system.  The roofs are bonded to the support posts and support posts are connected to earth pits as per		

4.7	Each commuter facilities structures for POB, covered linkway, bus shelters, etc. are provided with an independent lightning protection system, including earth pits.		9		
4.8	The lightning protection system between two or more commuter facilities structures, such as POB, covered linkway, bus shelters, etc. are bonded and electrically continuous.				
4.9	Earth pits are not in the path of commuter walkway.				
5.	Earthing System and Equipotential Bonding				
5.1	Earthing requirements is provided in accordance to SS 551.				
5.2	Equipotential bonding are provided in accordance to SS CP5 for all exposed metal parts and metallic street furniture.				
5.3	Equipotential bonding layout plans, sections and cable route to OG box are included.				
ē					
	Qualified Person (QP)	_	a la	Date	

Note: Please tick in appropriate box for all items.
This checklist is to be submitted for every submission/re-submission.

# M&E CHECKLIST FOR COVERED LINKWAY

Commuter Facilities and Systems Management (Maintenance Related)

	ect:	(√) Tic	k the approp	priate box for all it
	Standard Requirements	Yes	NA	Remarks
1.	General			
1.1	Summary list of proposed items, with brand & model, to be used on site.			
1.2	Electrical and lightning protection system installations embedded in the slab of PUB drains complied with LTA's requirements (if applicable).			
1.3	Consult LTA's Commuter Facilities & Systems Management if the roof alignment of the covered linkway affects any existing Street Lights.		9	
2.	Electrical Distribution			
2.1	Power supply source is standalone i.e. supply source does not come from building switch board or share with building system.			
2.2	The control switches/MCB for the different facilities are independent e.g. control switch for covered linkway only control the lightings within covered linkway.			
2.3	The OG box shall be located adjacent to the covered linkway and shall not in any way obstruct the view of motorists/road users.			
3.	Lighting Design and Light Fittings			
3.1	The mounting details of the light fittings to the covered linkway beams/columns are included.			
3.2	The light throw of the light fittings is not affected by beams/columns i.e. minimise the discrepancy between the simulated lux and completed site measured lux.			

Note: This checklist is to be submitted for every submission/re-submission.